(9	Α		I	O	_
	•	,,	•	_	~	`

QUERY CONTROL FORM			RTIS U	SE ONLY
Application No. 10/001 308	Prepared by	Lois Stone	Tracking Number	5917062
Examiner-GAU Valentine - 1742	Date	5/26/04	Week Date	3/8/04
	No. of queries		TFW.	, ,

JACKET						
a. Serial No.	f. Foreign Priority	k. Print Claim(s)	p. PTO-1449			
b. Applicant(s)	g. Disclaimer	I. Print Fig.	q. PTOL-85b			
c. Continuing Data	h. Microfiche Appendix	m. Searched Column	r. Abstract			
d. PCT	i. Title	n. PTO-270/328	s. Sheets/Figs			
e. Domestic Priority	j. Claims Allowed	o. PTO-892	t. Other			

SPECIFICATION	MESSAGE
a. Page Missing	Claim 14 (original claim 79) depends on
b. Text Continuity	Claim 14 (original claim 79) depends on claim 1 (original claim GE) and conceled
c. Holes through Data	claim 27. Please advise.
d. Other Missing Text	
e. Illegible Text	
f. Duplicate Text	
g. Brief Description	
h. Sequence Listing	
i. Appendix	
j. Amendments	
k. Other	
CLAIMS	
a. Claim(s) Missing	
b. Improper Dependency	Thank you.
c. Duplicate Numbers	
d. Incorrect Numbering	initials (L)
e. Index Disagrees	RESPONSE
f. Punctuation	
g. Amendments	
h. Bracketing	
i. Missing Text	
j. Duplicate Text	
k. Other	
	initials

- 78. The method of claim 76, wherein the produced aluminium continuously drains from said cathode.
- The method of claim 66, for producing aluminium in a bipolar cell according to claim 27, comprising passing an electric current from the surface of the terminal cathode to the surface of the terminal anode as ionic current in the electrolyte and as electronic current through the bipolar electrodes, thereby electrolysing the alumina dissolved in the electrolyte to produce aluminium on each cathode surface and oxygen on each anode surface.
- 80. The method of claim 66, comprising circulating the electrolyte between the anodes and facing cathodes thereby improving dissolution of alumina into the electrolyte and/or improving the supply of dissolved alumina under the active surfaces of the anodes.
- 81. A cell component which can be maintained dimensionally stable in a cell for the electrowinning of aluminium according to claim 1, having an iron oxide-based outside layer, in particular a hematite-based layer, which is electrochemically active for the oxidation of oxygen ions into molecular oxygen.
- 82. The cell component of claim 81, wherein the hematite-based layer covers a metal-based substrate comprising at least one metal, an alloy, an intermetallic compound or a cermet.